DELPHES, a framework for fast simulation of a general purpose LHC detector

S. Ovyn and X. Rouby^{*} Center for Particle Physics and Phenomenology (CP3) Université catholique de Louvain B-1348 Louvain-la-Neuve, Belgium

severine.ovyn@uclouvain.be, xavier.rouby@cern.ch

Abstract

Knowing whether theoretical predictions are visible and measurable in a high energy experiment is always delicate, due to the complexity of the related detectors, data acquisition chain and software. We introduce here a new framework, DELPHES, for fast simulation of a general purpose experiment. The simulation includes a tracking system, embedded into a magnetic field, calorimetry and a muon system, and possible very forward detectors arranged along the beamline. The framework is interfaced to standard file formats (e.g. Les Houches Event File) and outputs observable analysis data objects, like missing transverse energy and collections of electrons or jets. The simulation of detector response takes into account the detector resolution, and usual reconstruction algorithms for complex objects, like FASTJET. A simplified preselection can also be applied on processed data for trigger emulation. Detection of very forward scattered particles relies on the transport in beamlines with the HECTOR software. Finally, the FROG 2D/3D event display is used for visualisation of the collision final states. An overview of DELPHES is given as well as a few use-cases for illustration.

Keywords: DELPHES, fast simulation, LHC, smearing, trigger, FASTJET, HECTOR, FROG

1 Introduction

Experiments at high energy colliders are very complex systems, in several ways. First, in terms of the various detector subsystems, including tracking, central calorimetry, forward calorimetry, and muon chambers. These detectors differ with their principles, technologies, geometries and sensitivities. Then, due to the requirement of a highly effective online selection (i.e. a *trigger*), subdivided into several levels for an optimal reduction factor, but based only on partially processed data. Finally, in terms of the experiment software, with different data formats (like *raw* or *reconstructed* data), many reconstruction algorithms and particle identification schemes.

This complexity is handled by large collaborations of thousands of people, which restrict the

^{*}Now in Physikalisches Institut, Albert-Ludwigs-Universität Freiburg

availability of the data, software and documentation to their members. Real data analyses require a full detector simulation, including the various detector inefficiencies, the dead material, the imperfections and the geometrical details. Moreover, detector calibration and alignment are crucial. Such simulation is very complicated, technical and slow. On the other hand, phenomenological studies, looking for the observability of given signals, may require only fast but realistic estimates of the observables.

A new framework, called DELPHES [1], is introduced here, for the fast simulation of a general purpose collider experiment. Using the framework, observables can be estimated for specific signal and background channels, as well as their production and measurement rates, under a set of assumptions. Starting from the output of event generators, the simulation of the detector response takes into account the subdetector resolutions, by smearing the kinematical properties of the visible final particles. Tracks of charged particles and calorimetric towers (or *calotowers* are then created.

DELPHES includes the most crucial experimental features, like (1) the geometry of both central or forward detectors; (2) lepton isolation; (3) reconstruction of photons, leptons, jets, *b*-jets, τ jets and missing transverse energy; (4) trigger emulation and (5) an event display (Fig. 1).

Although this kind of approach yields much realistic results than a simple "parton-level" analysis, a fast simulation comes with some limitations. Detector geometry is idealised, being uniform, symmetric around the beam axis, and having no cracks nor dead material. Secondary interactions, multiple scatterings, photon conversion and bremsstrahlung are also neglected.

Three formats of input files can currently be used as input in DELPHES¹. In order to process events from many different generators, the standard Monte Carlo event structure StdHEP can be used as an input. Besides, DELPHES can also provide detector response for events read in "Les Houches Event Format" (LHEF) and ROOT files obtained using the **h2root** utility from the ROOT framework [7].

The output of DELPHES contains a copy of the generator level data (GEN tree), the analysis data objects after reconstruction (Analysis tree), and possibly the results of the trigger emulation (Trigger tree). The program is driven by input cards. The detector card (data/DataCardDet.dat) allows a large spectrum of running conditions by modifying basic detector parameters, including calorimeter and tracking coverage and resolution, thresholds or jet algorithm parameters. The trigger card (data/trigger.dat) lists the user algorithms for the simplified online preselection.

2 Detector simulation

The overall layout of the general purpose detector simulated by DELPHES is shown in Fig. 2. A central tracking system (TRACKER) is surrounded by an electromagnetic and a hadron calorimeters (ECAL and HCAL, resp.). Two forward calorimeters (FCAL) ensure a larger geometric coverage for the measurement of the missing transverse energy. Finally, a muon system (MUON) encloses the central detector volume The fast simulation of the detector response takes into account geometrical acceptance of sub-detectors and their finite resolution, as defined in the smearing data card^2 . If no such file is provided, predifined values are used. The coverage of the various subsystems used in the default configuration are summarised in table 1.

 $^{^1[\}texttt{code}]~$ See the <code>HEPEVTConverter</code>, <code>LHEFConverter</code> and <code>STDHEPConverter</code> classes.

²[code] See the RESOLution class.

Table 1: Default extension in pseudorapidity η of the different subdetectors. The corresponding parameter name, in the smearing card, is given.

TRACKER	CEN_max_tracker	$0.0 \le \eta \le 2.5$
ECAL, HCAL	CEN_max_calo_cen	$0.0 \le \eta \le 3.0$
FCAL	CEN_max_calo_fwd	$3.0 \le \eta \le 5.0$
MUON	CEN_max_mu	$0.0 \le \eta \le 2.4$



Figure 2: Profile of layout of the generic detector geometry assumed in DELPHES. The innermost layer, close to the interaction point, is a central tracking system (pink). It is surrounded by a central calorimeter volume (green) with both electromagnetic and hadronic sections. The outer layer of the central system (red) consist of a muon system. In addition, two end-cap calorimeters (blue) extend the pseudorapidity coverage of the central detector. The detector parameters are defined in the user-configuration card. The extension of the various subdetectors, as defined in Tab. 1, are clearly visible. The detector is assumed to be strictly symmetric around the beam axis (black line). Additional forward detectors are not depicted.

Magnetic field

In addition to the subdetectors, the effects of a dipolar magnetic field is simulated for the charged particles³. This simply modifies the corresponding particle direction before it enters the calorimeters.

2.1 Tracks reconstruction

Every stable charged particle with a transverse momentum above some threshold and lying inside the fiducial volume of the tracker provides a track. By default, a track is assumed to be reconstructed with 90% probability⁴ if its transverse momentum p_T is higher than 0.9 GeV and if its pseudorapidity $|\eta| \leq 2.5$.

2.2 Simulation of calorimeters

The energy of each particle considered as stable in the generator particle list is smeared, with a Gaussian distribution depending on the calorimeter resolution. This resolution varies with the subcalorimeter (ECAL, HCAL, FCAL) measuring the particle. The response of each sub-calorimeter is parametrised as a function of the energy:

$$\frac{\sigma}{E} = \frac{S}{\sqrt{E}} \oplus \frac{N}{E} \oplus C, \tag{1}$$

where S, N and C are the *stochastic*, *noise* and *constant* terms, respectively.

The particle four-momentum p^{μ} are smeared with a parametrisation directly derived from

³[code] See the TrackPropagation class.

⁴[code] The reconstruction efficiency is defined in the smearing datacard by the TRACKING_EFF term.

the detector techinal designs⁵. In the default parametrisation, the calorimeter is assumed to cover the pseudorapidity range $|\eta| < 3$ and consists in an electromagnetic and an hadronic part. Coverage between pseudorapidities of 3.0 and 5.0 is provided by forward calorimeters, with different response to electromagnetic objects (e^{\pm}, γ) or hadrons. Muons and neutrinos are assumed no to interact with the calorimeters⁶. The default values of the stochastic, noisy and constant terms are given in Table 2.

The energy of electrons and photons found in the particle list are smeared using the ECAL resolution terms. Charged and neutral final state hadrons interact with the ECAL, HCAL and FCAL. Some long-living particles, such as the K_s^0 , possessing lifetime $c\tau$ smaller than 10 mm are considered as stable particles although they decay before the calorimeters. The energy smearing of such particles is performed using the expected fraction of the energy, determined according to their decay products, that would be deposited into the ECAL $(E_{\rm ECAL})$ and into the HCAL $(E_{\rm HCAL})$. Defining Fas the fraction of the energy leading to a HCAL deposit, the two energy values are given by

$$\begin{cases}
E_{\text{HCAL}} = E \times F \\
E_{\text{ECAL}} = E \times (1 - F)
\end{cases}$$
(2)

where $0 \leq F \leq 1$. The electromagnetic part is handled as the electrons. The resulting final energy given after the application of the smearing is then $E = E_{\text{HCAL}} + E_{\text{ECAL}}$. For K_S^0 and Λ hadrons, the energy fraction is F is assumed to be worth 0.7.

Table 2: Default values for the resolution of the central and forward calorimeters. Resolution is parametrised by the *stochastic* (S), *noise* (N) and *constant* (C) terms (Eq. 1). The corresponding parameter name, in the smearing card, is given.

Resolution Term	Card flag	Value		
ECAL				
S	ELG_Scen	0.05		
N	ELG_Ncen	0.25		
C	ELG_Ccen	0.0055		
FCAL, electromagnetic part				
S	ELG_Sfwd	2.084		
N	ELG_Nfwd	0		
C	ELG_Cfwd	0.107		
HCAL				
S	HAD_Shcal	1.5		
N	HAD_Nhcal	0		
C	HAD_Chcal	0.05		
FCAL, hadronic part				
S	HAD_Shf	2.7		
N	HAD_Nhf	0.		
C	HAD_Chf	0.13		

2.3 Calorimetric towers

The smallest unit for geometrical sampling of the calorimeters is a *tower*; it segments the (η, ϕ) plane for the energy measurement. All undecayed particles, except muons and neutrinos produce a calorimetric tower, either in ECAL, in HCAL or FCAL. As the detector is assumed to be symmetric in ϕ and with respect to the $\eta = 0$ plane, the smearing card stores the number of calorimetric towers with $\phi = 0$ and $\eta > 0$ (default: 40 towers). For a given η , the size of the ϕ segmentation is also specified. Fig. 3 illustrates the default segmentation of the (η, ϕ) plane.

The calorimetric towers directly enter in the calculation of the missing transverse energy, and as input for the jet reconstruction algorithms. No longitudinal segmentation is available in the sim-

⁵[code] The response of the detector is applied to the electromagnetic and the hadronic particles through the SmearElectron and SmearHadron functions.

⁶In the current DELPHES version, particles other than electrons (e^{\pm}) , photons (γ) , muons (μ^{\pm}) and neutrinos $(\nu_e, \nu_{\mu} \text{ and } \nu_{\tau})$ are simulated as hadrons for their interactions with the calorimeters. The simulation of stable particles beyond the Standard Model should subsequently be handled with care.



Figure 3: Default segmentation of the calorimeters in the (η, ϕ) plane. Only the central detectors (ECAL, HCAL and FCAL) are considered.

ulated calorimeters. No sharing between neighbouring towers is implemented when particles enter a tower very close to its geometrical edge.

2.4 Very forward detectors simulation

Most of the recent experiments in beam colliders have additional instrumentation along the beamline. These extend the η coverage to higher values, for the detection of very forward final-state particles. Zero Degree Calorimeters (ZDC) are located at zero angle, i.e. are aligned with the beamline axis at the interaction point, and placed at the distance where the paths of incoming and outgoing beams separate (Fig. 4). These allow the measurement of stable neutral particles (γ and n) coming from the interaction point, with large pseudorapirities (e.g. $|\eta_{n,\gamma}| > 8.3$ in CMS). Forward taggers (called here RP220 and FP420 as at the LHC) are meant for the measurement of particles following very closely the beam path. To be able to reach these detectors, such particles must have a charge identical to the beam particles, and a momentum very close to the nominal value for the beam. These taggers are near-beam detectors located a few millimeters from the true beam trajectory and this distance defines their acceptance (Table 3).

While neutral particles propagate along a straight line to the ZDC, a dedicated simulation of the transport of charged particles is needed for



Figure 4: Default location of the very forward detectors, including ZDC, RP220 and FP420 in the LHC beamline. Incoming (red) and outgoing (black) beams on one side of the interaction point (s = 0 m). The Zero Degree Calorimeter is located in perfect alignment with the beamline axis at the interaction point, at 140 m, where the beam paths are separated. The forward taggers are near-beam detectors located at 220 m and 420 m.

RP220 and FP420. This fast simulation uses the HECTOR software [4], which includes the chromaticity effects and the geometrical aperture of the beamline elements.

Some subdetectors have the ability to measure the time of flight of the particle. This corresponds to the delay after which the particle is observed in the detector, after the bunch crossing. The time of flight measurement of ZDC and FP420 detector is implemented here. For the ZDC, the formula is simply

$$t = t_0 + \frac{1}{v} \times \left(\frac{s-z}{\cos\theta}\right),\tag{3}$$

where t is the time of flight, t_0 is the true time coordinate of the vertex from which the particle originates, v the particle velocity, s is the ZDC distance to the interaction point, z is the longitudinal

Table 3: Default parameters for the forward detectors: distance from the interaction point and detector acceptance. The LHC beamline is assumed around the fifth interaction point. For the ZDC, the acceptance depends only on the pseudorapidity η of the particle, which should be neutral and stable. The tagger acceptance is fully determined by the distance in the transverse plane of the detector to the real beam position [4]. It is expressed in terms of the particle energy.

Detector	Distance	Acceptance	
ZDC	140 m	$ \eta > 8.3$	for n and γ
RP220	$220 \mathrm{m}$	$E \in [6100; 6880] \text{ (GeV)}$	at 2 mm $$
FP420	$420 \mathrm{m}$	$E \in [6880; 6980] \text{ (GeV)}$	at 4 mm

coordinate of the vertex from which the particle comes from, θ is the particle emission angle. This assumes that the neutral particle observed in the ZDC is highly relativistic, i.e. travelling at the speed of light c. We also assume that $\cos \theta = 1$, i.e. $\theta \approx 0$ or equivalently η is large. As an example, $\eta = 5$ leads to $\theta = 0.013$ and $1 - \cos \theta < 10^{-4}$. The formula then reduces to

$$t = \frac{1}{c} \times (s - z) \tag{4}$$

Only neutrons and photons are currently assumed to be able to reach the ZDC. All other particles are neglected in the ZDC. To fix the ideas, if the ZDC is located at s = 140 m, neglecting z and θ , and assuming that v = c, one gets $t = 0.47 \ \mu$ s.

3 High-level object reconstruction

Analysis object data contain the final collections of particles $(e^{\pm}, \mu^{\pm}, \gamma)$ or objects (light jets, *b*jets, τ -jets, E_T^{miss}) and are stored⁷ in the output file created by DELPHES. In addition, some detector data are added: tracks, calorometric towers and hits in ZDC, RP220 and FP420. While electrons, muons and photons are easily identified, some other objects are more difficult to measure, like jets or missing energy due to invisible particles.

For most of these objects, their four-momentum p^{μ} and related quantities are directly accessible in DELPHES output $(E, \vec{p}, p_T, \eta \text{ and } \phi)$. Additional properties are available for specific objects (like the charge and the isolation status for e^{\pm} and μ^{\pm} , the result of application of *b*-tag for jets and time-of-flight for some detector hits).

3.1 Photon and charged lepton reconstruction

From here onwards, *electrons* refer to both positrons (e^+) and electrons (e^-) , and *charged leptons* refer to electrons and muons (μ^{\pm}) , leaving out the τ^{\pm} leptons as they decay before being detected.

Electrons and photons

Photon and electron (e^{\pm}) candidates are reconstructed if they fall into the acceptance of the tracking system and have a transverse momentum above a threshold (default $p_T > 10$ GeV). A calorimetric tower will be seen in the detector, an electrons leave in addition a track. Consequently, electrons and photons creates as usual a candidate in the jet collection.

 $^{^7 \}verb"[code]"$ All these processed data are located under the <code>Analysis</code> tree.

Muons

Generator level muons entering the detector acceptance are considered as candidates for the analysis level. The acceptance is defined in terms of a transverse momentum threshold to overpass (default : $p_T > 10$ GeV) and of the pseudorapidity coverage of the muon system of the detector (default: $-2.4 \leq \eta \leq 2.4$). The application of the detector resolution on the muon momentum depends on a Gaussian smearing of the p_T variable⁸. Neither η nor ϕ variables are modified beyond the calorimeters: no additional magnetic field is applied. In addition, multiple scattering is also neglected. This implies that low energy muons have in DELPHES a better resolution than in a real detector.

Charged lepton isolation

To improve the quality of the contents of the charged lepton collections, additional criteria can be applied to impose some isolation. This requires that electron or muon candidates are isolated in the detector from any other particle, within a small cone. In DELPHES, charged lepton isolation demands that there is no other charged particle with $p_T > 2$ GeV within a cone of $\Delta R = \sqrt{\Delta \eta^2 + \Delta \phi^2} < 0.5$ around the lepton. The result (i.e. *isolated* or *not*) is added to the charged lepton measured properties⁹.

3.2 Jet reconstruction

A realistic analysis requires a correct treatment of final state particles which hadronise. Therefore, the most widely currently used jet algorithms have been integrated into the DELPHES framework using the FASTJET tools [2]. Six different jet reconstruction schemes are available¹⁰. The first three belong to the cone algorithm class while the last three are using a sequential recombinaison scheme. For all of them, the towers are used as input of the jet clustering. Jet algorithms also differ with their sensitivity to soft particles or collinear splittings, and with their computing speed performance.

Cone algorithms

- 1. CDF Jet Clusters: Algorithm forming jets by associating together towers lying within a circle (default radius $\Delta R = 0.7$) in the (η, ϕ) space. The so-called JETCLU cone jet algorithm that was used by CDF in Run II is used. All towers with a transverse energy E_T higher than a given threshold (default: $E_T > 1$ GeV) are used to seed the jet candidates. The existing FASTJET code as been modified to allow easy modification or the tower pattern in η, ϕ space. In the following versions of DELPHES, a new dedicated plugin will be created on this purpose¹¹.
- 2. *CDF MidPoint*: Algorithm developped for the CDF Run II to reduce infrared and collinear sensitivity compared to purely seedbased cone by adding 'midpoints' (energy barycenters) in the list of cone seeds.
- 3. *SISCone*: Seedless Infrared Safe Cone [3]: Cone algorithm simultaneously insensitive to additional soft particles and collinear splittings, and fast enough to be used in experimental analysis.

Recombination algorithms

The three following jet algorithms are safe for soft radiations (*infrared*) and collinear splittings.

⁸[code] See the SmearMuon method.

⁹[code] See the IsolFlag output of the Electron or Muon collections in the Analysis tree.

¹⁰[code] The choice is done by allocating the JET_jetalgo input parameter in the smearing card.

¹¹[code] JET_coneradius and JET_seed variables in the smearing card.

They rely on recombination schemes where neighbouring calotower pairs are successively merged. The definitions of the jet algorithms are similar except for the definition of the *distances d* used during the merging procedure. Two such variables are defined: the distance d_{ij} between each pair of towers (i, j), and a variable d_{iB} (beam distance) depending on the transverse momentum of the tower i.

The jet reconstruction algorithm browses the calotower list. It starts by finding the minimum value d_{\min} of all the distances d_{ij} and d_{iB} . If d_{\min} is a d_{ij} , the towers *i* and *j* are merged into a single tower with a four-momentum $p^{\mu} = p^{\mu}(i) + p^{\mu}(j)$ (*E-scheme recombination*). If d_{\min} is a d_{iB} , the tower is declared as a final jet and is removed from the input list. This procedure is repeated until no input towers are left. Further information on these jet algorithms is given here below, using k_{ti} , y_i and ϕ_i as the transverse momentum, rapidity and azimuth of calotower *i* and $\Delta R_{ij} = \sqrt{(y_i - y_j)^2 + (\phi_i - \phi_j)^2}$ as the jet-radius parameter:

4. Longitudinally invariant k_t jet:

$$d_{ij} = \min(k_{ti}^2, k_{tj}^2) \Delta R_{ij}^2 / R^2 d_{iB} = k_{ti}^2$$
(5)

5. Cambridge/Aachen jet:

$$d_{ij} = \Delta R_{ij}^2 / R^2$$

$$d_{iB} = 1 \tag{6}$$

6. Anti k_t jet: where hard jets are exactly circular

$$d_{ij} = \min(1/k_{ti}^2, 1/k_{tj}^2)\Delta R_{ij}^2/R^2 d_{iB} = 1/k_{ti}^2$$
(7)

By default, reconstruction uses a cone algorithm with $\Delta R = 0.7$. Jets are stored if their transverse energy is higher¹² than 20 GeV.

3.3 b-tagging

A jet is tagged as *b*-jets if its direction lies in the acceptance of the tracker and if it is associated to a parent *b*-quark. A *b*-tagging efficiency of 40% is assumed if the jet has a parent *b* quark. For *c*-jets and light jets (i.e. originating in *u,d,s* quarks or in gluons), a fake *b*-tagging efficiency of 10% and 1% respectively is assumed¹³. The (mis)tagging relies on the true particle identity (PID) of the most energetic particle within a cone around the observed (η, ϕ) region, with a radius ΔR of 0.7.

3.4 τ identification

Jets originating from τ -decays are identified using an identification procedure consistent with the one applied in a full detector simulation [8]. The tagging rely on two properties of the τ lepton. First, 77% of the τ hadronic decays contain only one charged hadron associated to a few neutrals (table 4). Tracks are useful for this criterium. Secondly, the particles arisen from the τ lepton produce narrow jets in the calorimeter (*collimation*).

Table 4: Branching rations for τ^{-} lepton [11]. h^{\pm} and h^{0} refer to charged and neutral hadrons, respectively. $n \geq 0$ and $m \geq 0$ are integers.

Leptonic decays		
$\tau^- \to e^- \ \bar{\nu}_e \ \nu_\tau$	17.85%	
$ au^- ightarrow \mu^- \ ar{ u}_\mu \ u_ au$	17.36%	
Hadronic decays		
$\tau^- \to h^- \ n \times h^{\pm} \ m \times h^0 \ \nu_{\tau}$	64.79%	
$ au^- ightarrow h^- \ m imes h^0 \ u_ au$	50.15%	
$\tau^- \to h^- \ h^+ h^- m \times h^0 \ \nu_{\tau}$	15.18%	

¹³[code] Corresponding to the TAGGING_B, MISTAGGING_C and MISTAGGING_L constants, for (respectively) the efficiency of tagging of a *b*-jet, the efficiency of mistagging a *c*-jet as a *b*-jet, and the efficiency of mistagging a light jet (u,d,s,g) as a *b*-jet.

¹²[code] PTCUT_jet variable in the smearing card.



Figure 5: Illustration of the identification of τ -jets. The jet cone is narrow and contains only one track.

Electromagnetic collimation

To use the narrowness of the τ -jet, the *electro-magnetic collimation* C_{τ}^{em} is defined as the sum of the energy of towers in a small cone of radius $R^{\rm em}$ around the jet axis, divided by the energy of the reconstructed jet. To be taken into account, a calorimeter tower should have a transverse energy $E_T^{\rm tower}$ above a given threshold. A large fraction of the jet energy is expected in this small cone. This fraction, or collimation factor, is represented in Fig. 6 for the default values (see table 5).

Tracking isolation

The tracking isolation for the τ identification requires that the number of tracks associated to a particle with a significant transverse momentum is one and only one in a cone of radius R^{tracks} . This cone should be entirely pointing to the tracker to be taken into account. Default values of these parameters are given in table 5.



Figure 6: Distribution of the electromagnetic collimation C_{τ} variable for true τ -jets, normalised to unity. This distribution is shown for associated WH photoproduction [9], where the Higgs boson decays into a W^+W^- pair. Each W boson decays into a $\ell\nu_{\ell}$ pair, where $\ell = e, \mu, \tau$. Events generated with MadGraph/MadEvent [10]. Histogram entries correspond to true τ -jets, matched with generator level data.

Purity

Once both electromagnetic collimation and tracking isolation are applied, a threshold on the p_T of the τ -jet candidate is requested to purify the collection. This procedure selects τ leptons decaying hadronically with a typical efficiency of 60%.

3.5 Transverse missing energy

In an ideal detector, momentum conservation imposes the transverse momentum of the observed final state p_T^{obs} to be equal to the p_T sum of the invisible particles, written p_T^{miss} .

$$p_T^{\text{miss}} = -p_T^{\text{obs}} \tag{8}$$

In a real experiment, energy is measured by calorimetry and any problem affecting the detector (dead channels, misalignment, noisy towers, cracks) worsens directly the measured miss-



Figure 7: Distribution of the number of tracks N^{tracks} within a small jet cone for true τ -jets, normalised to unity. Photoproduced WH events, where W bosons decay leptonically (e, μ, τ) , as in Fig. 6. Histogram entries correspond to true τ -jets, matched with generator level data.

ing transverse energy E_T^{miss} . In this document, missing transverse energy is based on the calorimetric towers and only muons and neutrinos are not taken into account for its evaluation:

$$E_T^{\text{miss}} = -\sum_i^{\text{towers}} E_T(i) \tag{9}$$

4 Trigger emulation

New physics in collider experiment are often characterised by the phenomenology by low crosssection values. High statistics are required for their studies, which in turn imposes high luminosity collisions.

On the other hand, due to the very high collision rate in recent collider (40 MHz at the LHC) and the large total cross-section ($\mathcal{O}(110 \text{ mb})$ at the LHC), the need for an online event selection is crucial in order to reject most of the event and keep Table 5: Default values for parameters used in τ -jet reconstruction algorithm. Electromagnetic collimation requirements involve the inner *small* cone radius R^{em} , the minimum transverse energy for calotowers E_T^{tower} and the collimation factor C_{τ} . Tracking isolation constrains the number of tracks with a significant transverse momentum p_T^{tracks} in a cone of radius R^{tracks} . Finally, the τ -jet collection is purified by the application of a cut on the p_T of τ -jet candidates.

Parameter	Card flag	Value			
Electromagnetic collimation					
R^{em}	TAU_energy_scone	0.15			
min E_T^{tower}	JET_M_seed	$1.0 \mathrm{GeV}$			
C_{τ}	TAU_energy_frac	0.95			
Tracking isolation					
R^{tracks}	TAU_track_scone	0.4			
min p_T^{tracks}	PTAU_track_pt	$2 { m GeV}$			
au-jet candidate					
$\min p_T$	TAUJET_pt	$10~{\rm GeV}$			

5 Validation

5.1 Jet resolution

The majority of interesting processes at the LHC contain jets in the final state. The jet resolution obtained using DELPHES is therefore a crucial point of the validation. While DELPHES contains six jet reconstruction algorithms, only the jet clustering algorithm with R = 0.7 is used to validate the jet collection. Cross-check has been made with the results obtained using the CMS detector. This validation employs $pp \rightarrow qq$ events produced using MG/ME and hadronized using PYTHIA. The events were divided into 14 bins of \hat{p}_T of the gluons. Each DELPHES jet is matched to the closest particle-level jet using the spatial separation in $\eta - \phi$ between the two jet axis $\Delta R < 0.25$, otherwise they are discarded. The particle-level jets are obtained by applying the same clustering algorithm to all particles considered as stable by PYTHIA.

For each \hat{p}_T bin, the DELPHES jet transverse energy (E_T^{rec}) of all jets satisfying the matching criteria is compaired to the *particle level* transverse energy (E_T^{MC}) . The obtained histograms of the E_T^{rec}/E_T^{MC} response have been fitted with a Gaussian function in the interval $\pm 2.RMS$ centered around the mean value. The final jet resolution is obtained using the following formula:

$$\frac{\sigma(R_{jet})}{\langle R_{jet} \rangle} = \frac{\sigma(\frac{E_T^{rec}}{E_T^{MC}})_{fit}}{\langle \frac{E_T^{rec}}{E_T^{MC}} \rangle_{fit}}.$$
 (10)



Figure 8: Distribution of the jet transverse energy resolution as a function of the *particle-level* jet transverse energy. The maximum allowed separation between the DELPHES and the *partile-level* jets is $\Delta R < 0.25$.

The resulting jet resolution, plotted as a function of E_T^{GEN} is shown in figure 8. The plots were then fitted with a function of the following form:

$$\frac{a}{E_T^{GEN}} \oplus \frac{b}{\sqrt{E_T^{GEN}}} \oplus c, \tag{11}$$

where a, b, and c are the fit parameters. The obtained resolution is compared to the one obtained with a recent version of the simulation package of the CMS detector. Overall, the resolution curve of DELPHES matches relatively well to those of CMS.

5.2 E_T^{mis} resolution

Because all major detectors at hadron colliders have been designed to be as mutch hermetic as possible in order to detect the presence of one or more neutrinos through apparent missing transverse energy, the resolution of the E_T^{miss} obtained with DELPHES is a crucial point. The samples used to study the transverse missing energy performance are identical to those used for the jet validation. The *particle-level* true transverse missing energy is calculated as the vector sum of the transverse momenta of all visible particles (or equivalently, to the vector sum of invisible particles). It should be noticed that the contribution to the transverse missing energy from muons is negligeable in the sample we are interested in.

In order to obtain the x-component missing energy resolution (E_x^{miss}) , the distribution of the difference between the DELPHES and the *particlelevel* E_x^{miss} has been fitted with a Gaussian function. The resulting E_x^{mis} is plotted in figure 9 as a function of the total visible transverse energy, defined as the scalar sum of transverse energy in all towers (ΣE_T) .

The resolution is observed to follow the form

$$\sigma_X = \alpha \ \Sigma E_T \ \text{GeV}^{1/2},\tag{12}$$

whith α is depending on the resolution of the calorimeters. Knowing that the expected transverse missing energy resolution expected using the CMS detector for similar events is $\sigma_X = (0.6 - 0.7) \Sigma E_T \text{ GeV}^{1/2}$ with no pile-up (no extra simultaneous pp collision occuring at the same bunch crossing), we can conclude that the resolution obtained by DELPHES ($\sigma_X = 0.68 \Sigma E_T \text{ GeV}^{1/2}$) is in excellent agreement with the expectations of a general purpose detector.



Figure 9: $\sigma(E_x^{miss})$ as a function on the scalar sum of all towers (ΣE_T) for $pp \to gg$ events.

5.3 *tau*-jet efficiency

with an efficic iency of about 50% for the τ -jets in CMS [12].

6 Visualisation

As an illustration, an associated photoproduction of a W boson and a t quark is shown in Fig. 12. This corresponds to a $pp \to Wt + p + X$ process, where the Wt couple is induced by an incoming photon emitted by one interacting proton. This leading proton survives from the photon emission and subsequently from the pp interaction, and is present in the final state. The experimental signature is a lack of hadronic activity in one forward hemisphere, where the surviving proton escapes. The t quark decays into a W and a b. Both W bosons decay into leptons ($W \to \mu \nu_{\mu}$ and $W \to \tau \nu_{\tau}$).

7 Conclusion and perspectives

References

[1] Delphes, hepforge:



Figure 10: Layout of the generic detector geometry assumed in DELPHES. The innermost layer, close to the interaction point, is a central tracking system (pink). It is surrounded by a central calorimeter volume (green) with both electromagnetic and hadronic sections. The outer layer of the central system (red) consist of a muon system. In addition, two end-cap calorimeters (blue) extend the pseudorapidity coverage of the central detector. The actual detector granularity and extension is defined in the user-configuration card. The detector is assumed to be strictly symmetric around the beam axis (black line). Additional forward detectors are not depicted.



Figure 11: Layout of the generic detector geometry assumed in DELPHES. Open 3D-view of the detector with solid volumes. Same colour codes as for Fig. 10 are applied. Additional forward detectors are not depicted.

[2] FAST-JET,

[3] A practical Seedless Infrared-Safe Cone jet algorithm, G.P. Salam, G. Soyez, JHEP0705:086,2007.



Figure 12: Example of $pp(\gamma p \to Wt)pY$ event. One W boson decays into a $\mu \nu_{\mu}$ pair and the second one into a $\tau \nu_{\tau}$ pair. The surviving proton leaves a forward hemisphere with no hadronic activity. The isolated muon is shown as the blue vector. The τ -jet is the cone around the green vector, while the reconstructed missing energy is shown in gray. One jet is visible in one forward region, along the beamline axis, opposite to the direction of the escaping proton.

- [4] HECTOR,
- [5] Frog,
- [6] CMS IN 2007/053
- [7] ROOT An Object Oriented Data Analysis Framework, R. Brun and F. Rademakers, Nucl. Inst. & Meth. in Phys. Res. A 389 (1997) 81-86, http://root.cern.ch
- [8] Tau reconstruction in CMS
- [9] WH photoproduction, S. Ovyn
- [10] Madgraph/Madevent
- [11] C. Amsler et al. (Particle Data Group), PL B667, 1 (2008) (URL: http://pdg.lbl.gov)
- [12] R. Kinnunen, Study of τ -jet identification in CMS, CMS NOTE 1997/002.



Figure 1: Flow chart describing the principles behind DELPHES. Event files coming from external Monte Carlo generators are read by a convertor stage. The kinematical variables of the final state particles are then smeared according to the subdetector resolutions. Tracks are reconstructed in a simulated dipolar magnetic field and calorimetric towers sample the energy deposits. Based on these, dedicated algorithms are applied for particle identification, isolation and reconstruction. The transport of very forward particle to the near-beam detectors is also simulated. Finally, an output file is written, including generator level and analysis object data. If requested, a fully parametrisable trigger can be emulated. Optionnally, the geometry and visualisation files for the 3D event display can also be produced. All user parameters are set in the *Smearing Card* and the *Trigger Card*.

A User manual

The available code is a tar file which comes with everything you need to run the DELPHES package. Nevertheless in order to visualise the events with the FROG program, you need to install libraries as explained in href="http://projects.hepforge.org/frog/">http://projects.hepforge.org/frog/

A.1 Getting started

In order to run DELPHES on your system, first download is sources and compile it:

```
me@mylaptop:~$ wget http://www.fynu.ucl.ac.be/users/s.ovyn/files/Delphes_V_*.*.tar
me@mylaptop:~$ tar -xvf Delphes_V_*.*. tar
me@mylaptop:~$ cd Delphes_V_*.*
me@mylaptop:~$ ./genMakefile.tcl > Makefile
me@mylaptop:~$ make
```

A.2 Running Delphes on your events

A.2.1 Setting the run configuration

The program is driven by two datacards (default cards are data/DataCardDet.dat and data/trigger.dat) which allow a large spectrum of running conditions. The run card

Contains all needed information to run DELPHES

- The following parameters are available: detector parameters, including calorimeter and tracking coverage and resolution, transverse energy thresholds allowed for reconstructed objects, jet algorithm to use as well as jet parameters.
- Four flags, FLAG_bfield, FLAG_vfd, FLAG_trigger and FLAG_frog should be assigned to decide if the magnetic field propagation, the very forward detectors acceptance, the trigger selection and the preparation for FROG display respectively are running by DELPHES.
- An example (the default detector card) can be found in files/DataCardDet.dat

The trigger card

Contains the definition of all trigger bits

- Cuts can be applied on the transverse momentum of electrons, muons, jets, tau-jets, photons and transverse missing energy.
- Be careful that the following structured should be used:
 - 1. One trigger bit per line, the first entry in the line is the name of the trigger bit
 - 2. If the trigger bit uses the presence of multiple identical objects, their transverse momentum thresholds must be defined in decreasing order
 - 3. The different object requirements must be separated by a && flag

4. Example of a trigger bit line:

DoubleElec >> ELEC1_PT: '20' && ELEC2_PT: '10'

• An example (the default trigger card) can be found ja href="files/trigger.dat" title="Home"¿herej/a¿j/li¿

A.2.2 Running the code

Create the above cards (data/mydetector.dat and data/mytrigger.dat) Create a text file containing the list of input files that will be used by DELPHES (with extension *.lhe, *.root or *.hep) To run the code, type the following

me@mylaptop:~\$./Delphes inputlist.list OutputRootFileName.root data/mydetector.dat data/mytr

A.3 Running an analysis on your Delphes events

Two examples of codes running on the output root file of DELPHES are coming with the package

1. The Examples/Analysis_Ex.cpp code shows how to access the available reconstructed objects and the trigger information The two following arguments are required: a text file containing the input DELPHES root files to run, and the name of the output root file. To run the code:

./Analysis_Ex input_file.list output_file.root

2. The Examples/Trigger_Only.cpp code permits to run the trigger selection separately from the general detector simulation on output DELPHES root files. An input DELPHES root file is mandatory as argument. The new tree containing the trigger information will be added in these file. The trigger datacard is also necessary. To run the code:

./Trigger_Only input_file.root data/trigger.dat

A.4 Running the Frog event display

- If the FLAG_frog was switched on, two files were created during the run of DELPHES: DelphesToFrog.vis and DelphesToFrog.geom. They contain all the needed information to run frog.
- To display the events and the geometry, you first need to compile FROG. Go to the Utilities/FROG and type make.
- Go back into the main directory and type ./Utilities/FROG/frog.

In the list of input files, all files should have the same type

in other words, the effect related to the particle showers that would happen in the calorimeters are not taken into account.